

Factory: Plot No. 457, 458, Vill. Matoda, Bavla Road, Ta. Sanand, Dist. Ahmedabad. Pin - 382 210.

Date: 06.01.2014

To,
Government Of India,
Ministry of Environment & Forests,
Regional Office, Western Region,
Kendriya Paryavaran Bhavan,
Link Road No.3, Ravi Shankar Nagar,
BHOPAL-462016 (M.P.)

Kind Attn.: Dr. A. Mehrotra - Director (s)

Dear Sir,

Sub.: submission of compliance report of our site plot no. 191, Village: Chacharwadi Vasana, Taluka: Sanand, District: Ahmedabad.

Ref.: MoEF letter F. No.- J-11011/493/2009-IA.II (I) dated 25.08.2011

This has reference to the above stated subject and reference we submit half yearly compliance report to your office. Also attached lastest CCA order copy obtained from Gujarat Pollution Control Board. We hope that stated information and attached documents are as per your requirement.

Thanking you, Yours faithfully,

For, Intas Pharmaceuticals Limited.

Authorized Signatory

Encl.: As Above.



Factory: Plot No. 457, 458, Viil. Matoda, Bavla Road, Ta. Sanand, Dist. Ahmedabad. Pin - 382 210.

COMPLIANCE REPORT WITH RESPECT TO ENVIRONMENTAL CLEARANCE (APRIL 2012 - SEPTEMBER 2013)

Intas Pharmaceuticals Limited.

Site: Plot no. 191, Village: ChacharwadiVasana, Taluka: Sanand, Dist:
Ahmedabad

A. SPECIFIC CONDITIONS

	SPECIFIC CONDITIONS	OUR COMPLIANCE
i)	National Emission Standards for Organic Chemicals Manufacturing Industry issuedby the Ministry vide G.S.R. 608(E) dated 21st July, 2010 and amended time to time shall be followed by the unit.	We will keep update on guideline and we will follow and control all emission standard as per guideline.
ii)	As proposed, packed column scrubber consisting of ventury followed by alkali scrubber shall be provided to process vents to control HCI emissions within the limit prescribed by CPCB/GPCB. Packed column scrubber consisting of venturi followedby water scrubber shall be provided to control solvent vapours. The scrubbing media shall be sent to effluent treatment plant (ETP) for treatment. Efficiency of scrubber shall be monitored regularly and maintained properly. At no time, the emission levels shall go beyond the prescribed standards. In the event of failure of any pollution control system adopted by the unit, the respective unit shall not be restarted until the control measures are rectified to achieve the desired efficiency.	We have installed packed column scrubber consisting of ventury followed by alkali scrubber to process vents to control HCI emissions within the limit prescribed by CPCB/GPCB. As directed we are sending all scrubbing media to ETP for treatment. We are monitoring stack emissions regularly and as directed in event of any failure in system we will ensure desired efficiency prior to restart.
iii)	No steam boiler shall be installed for the proposed project as steam shall be made available for process from the existing adjoining plant of M/s INTAS PharmaceuticalsLtd.	Our company will take the steam from the adjoining plant as per approval.



Factory: Plot No. 457, 458, Vill. Matoda, Bavla Road, Ta. Sanand, Dist. Ahmedabad. Pin - 382 210.

	· · · · · · · · · · · · · · · · · · ·	T"
iv)	Ambient air quality data shall be collected as per NAAQES standards notified by the Ministry vide G.S.R. No.826(E) dated16th September, 2009. The levels of PM1o, SO2, NOx, CO, VOC and HCI shall be monitored in the ambient air and emissions from the stacks shall be monitored and displayed at a convenient location near the main gate of the company and at important public places. The company shall upload the results of monitored data on its website and shall update the same periodically. It shall simultaneously be sent to the Regional office of MOEF, the respective Zonal office of CPCB and Gujarat Pollution Control Board (GPCB). On-line VOC analyzer shall be installed for monitoring of VOCs in the ambient air.	We are regularly monitoring SO2, NOx, HCI emissions and maintaining records. We regularly submit the same to the regional office of MOEF and regional office of Gujarat Pollution Control Board. Stack monitoring will be carried out regularly and data for the same will be displayed near the main gate of the company and also uploaded on company's website periodically. We will install on-line VOC analyzer for monitoring of VOCs in the ambient air.
V)	In plant control measures for checking fugitive emissions from all the vulnerablesources shall be provided. Fugitive emissions shall be controlled by providing closed storage, closed handling & conveyance of chemicals/materials, multi cyclone separator and water sprinkling system. Dust suppression system including water sprinkling system shall be provided at loading and unloading areas to control dust emissions. Fugitive emissions in the work zone environment, product, raw materials storage area etc. shall be regularly monitored. The emissions shall conform to the limits stipulated by the GPCB.	All our raw materials, products and hazardous chemicals will be transferred in a closed system to reduce the fugitive emissions.



Factory: Plot No. 457, 458, Vill. Matoda, Bavla Road, Ta. Sanand, Dist. Ahmedabad. Pin - 382 210.

vi)	For further control of fugitive emissions, following steps shall be followed: 1.Closed handling system shall be provided for chemicals. 2.Reflux condenser shall be provided over reactor. 3. System of leak detection and repair of pump/pipeline based on preventive maintenance. 4. The acids shall be taken from storage tanks to reactors through closed pipeline. Storage tanks shall be vented through trap receiver and condenser operated on chilled water. 5. Cathodic protection shall be	 We have closed transfer system for chemicals. Reflux condesors are provided on all reactors. We have preventive maintenance schedule for all equipments. We do not have storage tanks for acid. We do not have under ground storage tanks.
	provided to the underground solvent storage tanks.	
vii)	The gaseous emissions from DG set shall be dispersed through adequate stackheight as per CPCB standards. Acoustic enclosure shall be provided to the DG sets to mitigate the noise pollution.	DG set is installed and we will monitor the emission as per the CPCB guideline. Acoustic enclosure is also provided.
viii)	Solvent management shall be carried out as follows: i.Reactor shall be connected to chilled brine condenser system ii. Reactor and solvent handling pump shall have mechanical seals to prevent leakages. iii. The condensers shall be provided with sufficient HTA and residence time so as to achieve more than 95% recovery. iv. Solvents shall be stored in a separate space specified with all safety measures. v. Proper earthing shall be provided in all the electrical equipment wherever solvent handling is done. vi. Entire plant shall be flame proof. The solvent storage tanks shall be provided with breather valve to prevent losses.	 All reactors are connected to chilled water and brine condenser system All solvent handling pumps are with mechanical seal. All condensers are designed with sufficient HTA based on process data. We have separate solvent storagearea as per explosive guideline. All equipments are provided earthing where ever solvent handling is done. In Manufacturing area all electrical fittings are flame proof. We do not have storage tanks for storage of solvents.



Factory: Plot No. 457, 458, Viil. Matoda, Bavla Road, Ta. Sanand, Dist. Ahmedabad. Pin - 382 210.

ſ	:\		
	xi)	Industrial effluent generation shall not exceed 14.65 m3/day. Industrial effluent shall be segregated into high COD and low COD effluent streams. High COD effluent stream shall be treated in MEE. Low COD effluent stream shall be treated in ETP and treated effluent shall be recycled and reused within the factory premises after achieving desirable water quality for various purposes. Sewage shall be disposed through septic tank followed by soak pit.	We are following the said system. We have installed adequate capacity effluent treatment plant for low COD stream and adequate capacity MEE for treatment of high COD effluent stream. Sewage is disposed through septic tank followed by soak pit.
	x)	Hazardous chemicals shall be stored in tanks, tank farms, drums, carboys etc. Flame arresters shall be provided on tank farm. Solvent transfer shall be by pumps.	At present we do not have any storage tanks for acid and solvent.
	xi)	As proposed, ETP sludge shall be sent to the TSDF. Process residue (organic), solvent residue and spent carbon will be sent to the cement plant.	ETP sludge will be sent to the GPCB approved TSDF site.



Factory: Plot No. 457, 458, Vill. Matoda, Bavla Road, Ta. Sanand, Dist. Ahmedabad. Pin - 382 210.

xii)	The Company shall strictly comply with the rules and guidelines under Manufacture, Storage and Import of Hazardous Chemicals (MSIHC) Rules, 1989 as amended time to time. All Transportation of Hazardous Chemicals shall be as per the Motor Vehicle Act (MVA), 1989.	Our company will comply with the said condition as directed.
xiii)	Entire plant where solvents are used shall be flame proof. The solvent storage tanks shall be provided with breather valve to prevent losses.	In Manufacturing area all electrical fittings are flame proof. We do not have storage tanks for storage of solvents.
xiv)	The company shall undertake following waste minimization measures: a. Metering and control of quantities of active ingredients to minimize waste. b. Reuse of by-products from the process as raw materials or as raw material substitutes in other processes. c. Use of automated filling to minimize spillage. d. Use of Close Feed system into batch reactors. e. Venting equipment through vapour recovery system. f. Use of high pressure hoses for equipment clearing to reduce wastewater generation.	We will comply all measures to minimize the waste generation as per the given direction. With continues R & D company will try to improve the process and minimize waste of active ingredients. We will reuse by products from the process where ever it is possible. We will install adequate system for close transfer to minimize spillage. All equipments venting is through vapour condensers and vapour recovery system. We have adequate high pressure cleaning system to reduce waste water generation.
xv)	The unit shall make the arrangement for protection of possible fire hazards during manufacturing process in material handling. Fire fighting system shall be as per the OISD 117 norms	Fire fighting system installation is completed & made proper arrangement for protection of possible fire hazards.
xvi)	Occupational health surveillance of the workers shall be done on a regular basis and records maintained as per the Factories Act.	Regular health check-up and programs are undertaken and carried out at regular interval.
xvii)	Green belt shall be developed in Selection of plant species shall be as per the CPCB guidelines.	Green belt area is under development as per guide line.